

# 영 문 규 격 서

## COMMODITY DESCRIPTION

관세분류번호 HSK NO.	품목 번호 ITEM NO.	품목 및 규격 DESCRIPTION	단 위 UNIT	수량 QUANTITY
		<b>Hemostasis Analyzer</b>	SYSTEM	1

### A. Features:

1. Hemostasis Analyzer system provides rapid, comprehensive and accurate identification of an individual's hemostasis condition which allows clinicians to drive personalized, clinically and economically sound treatment and monitoring decisions with confidence
2. Hemostasis Analyzer system is designed to allow targeted blood therapy to optimize clinical outcomes, helping to reduce costs
3. Reduce unnecessary transfusions
4. Reduce surgical exploration for bleeding
5. Provide rapid results in time to make decisions
6. Easy-to-use solution includes the analyzer, all-in-one test cartridges
7. Hemostasis Analyzer software enable the real-time data with the ability to transfer to/from LIS/HIS system
8. Simple, self-contained cartridge system
9. Test preparation without complex pipetting and mixing
10. Smaller blood volume per test
11. Comprehensive hemostasis analysis including true platelet function
12. Small footprint
13. Provides more information than routine coagulation tests
14. Vibration resistant
15. Robust self-monitoring quality control

### B. Specifications:

- 1) Hemostasis Analyzer

Sample volume	340 $\mu$ L
Measuring technique	Resonance–frequency viscoelasticity measurements Disposable Multi–channel microfluidic cartridge
Display	Backlit color LCD , 640x480 resolution Integrated 4–wire touch screen
Dimensions (W x L x H)	Width: 175mm (6.9 in) Length: 257mm (10.1 in) Height: 270mm (10.6 in)
Weight	4.2 kg (9.4 lbs.)
Operating Temperature	10°C to 32°C (50°F to 89.6°F)
Operating Pressure	0 to 2,000 m (0 to 6,560 ft) above sea level
Operating humidity	20% to 80% RH (non–condensing)
Voltage Rating	100V–240V AC
Power Supply Output	12 volts DC
Voltage	
Output Power / Current	5 A, 60 W (max)
Rating	
Supply Frequency	50/60 Hz
Replaceable Fuse – 5 Amp	Manufacturer: SIBA, P/N: GZ179021–5A, 5mm x 20mm, Quick–Action Ceramic, UL Recognized E167295

## 2) Accessories (Cartridges)

Description Item Code

Citrated: K, KH, RT, FF (10/box) 07–601

## C. Consists of:

1. Thrombelastography Hemostasis Analyzer ..... 1set
2. Citrated Multichannel Cartridges ..... 5ea
3. User’s Manual, Site Administrator’s Guide..... 1set
4. LIS Interface ..... 1set

## D. Remark:

1. The installation and operation service of the equipment shall be performed by the qualified / certified engineer at the end–user's site at free of charge.
2. Three years’ warranty should be provided after the performance test.
3. The supplier should provide training for a doctor and biomedical engineer.

※ 본 규격서와 다른 동등이상인 물품을 공급하고자 할 경우에는 물품의 규격, 품질 등이 특 정된 조건과 항목별 비교 서류로 동등이상임을 입증하여 규격 심사에서 “적합” 통과가 되어 야만 입찰에 참가(적용)할 수 있습니다.

진단검사의학과장 박 도 심 